# Declaration of properties in accordance with Regulation (EU) 305/2011

No. 1400 - CPR-2015/10/15

## 1. Unique identification code of product type:

The appliance for solid fuel with the supply of hot water EN 13229:2001 /A2:2004/AC:2007

2. Type, series and series number or any other element which allows identification of construction products: Fireplace inserts for wood type designation series BeF Aquatic WH 70 (individual designation in the chart below) designated for discontinuous use – classification of fireplace inserts 1b. according to the chart 1 EN 13229/A2.

## Main technical data of the fireplace insert

Туре	Main dimensions (mm)			Nominal output (kW)	Fuel consumption (kg/h)	Smoke flue diameter (mm)	Feed pressure (Pa)
	height	width	depth	, ,	wood		
BeF Aquatic WH 70	1410	712	486	11/8	3	150	12
BeF Aquatic WH V	1593	901	521	11/8	3	150	12

Other details are stated in the catalogue of the producer.

## 3. Intended use of construction product in accordance with relevant harmonized technical specification

Fireplace inserts for wood type designation series BeF Aquatic is designated for heating of living and common rooms. The product is designated for discontinuous use – classification of fireplace inserts 1b. according to the chart 1 EN 13229/A2.

#### 4. Name, company or registered trademark and contact address of the producer:

Company name: BeF Home, s.r.o.

Headquarters: Kotvrdovice 277

679 07, Kotvrdovice

Czech Republic

ID: 25524682

Tel.: +420 516 428 240 Fax: +420 516 428 244 E-mail: info@bef.cz

## 5. System of assessment and verification of constancy of construction products:

3 (attachment V, article 1.4 Regulation of the European Parliament and Council (EU) n. 305/2011 from 9. 3. 2011)

# 6. The products are covered by a harmonized standard:

EN 13229:2001 /A2:2004/AC:2007, assessment by system 3 was conducted by Engineering test institute, s.p., Hudcova 424/56b, 621 00 Brno, notified subject 1015 and it issued a test report type n. 1015-CPR-30-12638 of 15.10.2015

# $\label{eq:continuous} \textbf{7. Declared properties listed in the declaration apply for all products listed in article 2:}$

Harmonizedd technical specification	EN 13229:2001/A2:2004/AC:2007
Basic characteristics	Vlastnosti
Fire safety	Comply with ČSN EN 13229/A2:2005 čl.4.2, 4.3,4.7,4.8,4.10,4.11,4.15,5.2,5.5,6.11

Distance to flammable materials	Minimal distance, mm			
	Rear wall = 200			
	Side walls = 150			
	ceiling =1500			
	front wall = 800			
The risk of burning fuel falling out	Pass			
Flue gas emissions	CO [0.0911 %]			
Surface temperature	Pass			
Electrical safety	NPD			
Cleanability	Pass			
Max. working pressure	NPD			
Flue gas temperature at nominal heat output	T [169 °C]			
Mechanical resistance (capacity of exhaust neck)	NPD			
Heat output				
Nominal heat output	11 kW			
Output into air	2 kW			
Output into water	8 kW			
Energetic efficiency	η [87 %]			

# 8. Properties of the product listed in article 1 and 2 are in accordance with properties listed in article 7.

This declaration of properties is issued under the sole responsibillity of the manufacturer listed in article 4.

Signed for and on behalf of manufacturer:

Bc. Ing. Pavel Trubáček, MBA

General manager

In Kotvrdovicích, 1.12.2015

